



JP2	
P1	12V
P2	GND
P3	VIDEO
P4	GND

JP1	
P1	BLC ON/OFF
P2	ATW / AWB
P3	MIRROR
P4	2X ZOOM
P5	GND

SPECIFICATIONS

Image Sensor	1/3" CCD
PICTURE ELEMENTS	EIA: 512H x 492V, CCIR: 512H x 582V
HORIZONTAL RESOLUTION	420 Lines
Min Illumination	0.1 Lux
HORIZ. SYNC.FREQUENCY	EIA: 15.734KHz - CCIR: 15.625KHz
VERTICAL FREQUENCY	EIA: 60Hz - CCIR: 50Hz
CLOCK FREQUENCY	EIA: 19.0699MHz - CCIR: 18.9375MHz
SCANNING SYSTEM	2:1 INTERLACE
S/N RATIO	46dB
ELECTRONIC SHUTTER	1/100,000 sec. (Linear)
LENS	Pinhole 5.5mm f3.5
VIDEO OUTPUT	1Vp-p, 75 Ohms
AUDIO OUTPUT	2Vp-p Max
GAMMA.	0.45
MIRROR REVERSE PICTURE	NO
DIGITAL ZOOM	NO
Dimensions	32 x 32 mm
POWER SUPPLY	12VDC (+ / - 0.5V) @100ma
STORAGE TEMPERATURE	-30 to +60°C
OPERATING TEMPERATURE	-10 to +45°C