



### CD55NVIP - Network High Speed Dome Day & Night Dome

<b>Image sensor:</b>	1/4" IT CCD
<b>Synchronization:</b>	Internal
<b>White Balance:</b>	Auto/Manual
<b>Horizontal resolution:</b>	480 TVL
<b>Min. illumination:</b>	0.01Lux
<b>Focal length:</b>	f=4.1~73.8mm 18 X
<b>Focus &amp; Iris:</b>	Auto/Manual
<b>Pan speed:</b>	0°~240°/s
<b>Tilt speed:</b>	0°~120°/s
<b>Pan Speed :</b>	0~360° 15°/sec
<b>Pan range:</b>	360°continuously
<b>Tilt range:</b>	90°(180°auto overturn)
<b>Preset:</b>	64
<b>PIC:</b>	10M Ethernet(Ethernet 10 Base-T)
<b>Operational system:</b>	Embedded DSP
<b>Image format:</b>	MPEG4
<b>User:</b>	10 (max)
<b>Transmission:</b>	30 Frames/s
<b>Resolution:</b>	160x120

	320x240
	640x480
<b>Image quality:</b>	200 - 500 : 1
<b>Surveillance software:</b>	Special browse software
<b>Functions:</b>	Remote A/V recording
	Remote A/V playback
	Remote Surveillance
	Network bandwidth:100 ~ 1000Kbps
<b>Software:</b>	4-channel / 9-channel / 16-channel
	ActiveX
	* Pictures and specifications are subject to change without prior notice