



**CD55NV27 - 6" High Speed Color Dome 270X zoom Super HAD CCD (Day and Night) (color only optional) 480Lines Wall Bracket / Ceiling Bracket/ Heater Blower/ Power supply Included!**

|  |   |
|--|---|
| <b>Optical Technology Base:</b>              | HIGH RESOLUTION COLOR 1/4" SUPER HAD CCD      |
| <b>Picture Elements (Horz x Vert in mm):</b> | EIA/NTSC: 768H x 494V - CCIR/PAL: 752H x 582V |
| <b>Resolution:</b>                           | 480 Lines                                     |
| <b>Minimum Illumination:</b>                 | 0.1 Lux F1.6                                  |
| <b>S/N Ratio:</b>                            | >48 dB  |
| <b>Shutter Speed:</b>                        | 1/3~1/10000s                                  |
| <b>Zoom :</b>                                | 27X Optical 10X Digital                       |
| <b>Focus :</b>                               | Auto / Manual                                 |
| <b>Focal Length:</b>                         | f=4.1~73.8mm 18x                              |
| <b>Iris :</b>                                | Auto / Manual                                 |
| <b>Pan Speed :</b>                           | 0~300° /sec                                   |
| <b>Tilt Speed :</b>                          | 0~120° /sec                                   |
| <b>Pan Range :</b>                           | 360° continuously                             |
| <b>Tilt Range :</b>                          | 90° (180° overturn)                           |
| <b>Preset :</b>                              | 128 presets                                   |
| <b>White Balance / Gain / AE Control :</b>   | Auto / Manual                                 |
| <b>Video Output :</b>                        | 1V p-p, 75 ohms                               |
| <b>Communication :</b>                       | Multiprotocol, RS485                          |
| <b>Power Supply :</b>                        | AC24V +/- 1.50                                |
| <b>Weight :</b>                              | 2 Kg  |
| <b>Operating Temperature :</b>               | -35°C to +55°C (w/ Housing)                   |
| <b>Power Consumption :</b>                   | 20VA  |

\* Pictures and specifications are subject to change without prior notice