

Image Device	1/4" Interline CCD
Number of Pixels	NTSC : (H)510X(V)492 PAL : (H)500X(V)582
Scanning System	NTSC : 525 Lines, 60 Field/Sec PAL : 625 Lines, 50 Field/Sec
Sync System	Internal Synchronization
Horizontal Resolution	380 TV Line
Video output	1Vp-p 75 Ω , Negative
Audio output	
S/N Ratio	More Than 48dB (AGC OFF)
Gamma Characteristic	0.45
White Balance	Auto White Balance(AWB)
B.L.C	Back Light Compensation(Auto)
Minimum Illumination	1Lux (F:2.0)
Electronic Shutter	NTSC : 1/60~1/100,000 Sec PAL : 1/50~1/100,000 Sec
Built-in Lens	f : 3.6(Optional)
Power Consumption	12V \pm 10% DC, 100mA
Operation Temperature	-10 $^{\circ}$ C ~ + 50 $^{\circ}$ C , RH 95% Max
Storage Temperature	-20 $^{\circ}$ C ~ + 60 $^{\circ}$ C , RH 95% Max
Weight	Approx 100g
Housing	Aluminum
Color	Ivory or Black
Dimension (mm)	F 25X82
Cable	Standard 1m RCA/DC Jack
Mirror Image	Available