



CM25WNVB-S - SONY DSP 20 LED's IR Bullet Camera

Type:	Color CCD/ SONY DSP
Pick-up device:	1/4" CCD image sensor
Picture elements :	EIA/NTSC: 512 H x 492 V - CCIR/PAL: 512 H x 582 V
Horizontal resolution:	420 TVL
Minimun Illumination:	0 Lux (with IR on) 23 High Intensity IR Led's
Horizontal Sync. frequency:	EIA/NTSC: 15.734 KHZ - CCIR/PAL: 15.625 KHZ
Vertical frequency :	EIA/NTSC: 60 HZ - CCIR/PAL: 50 HZ
Clock frequency:	EIA/NTSC: 19.0699 MHZ - CCIR/PAL: 18.9375 MHZ
Scanning system:	2:1 interlace
S/N Ratio :	46 dB
Electronic shutter:	EIA/NTSC: 1/60 ~ 1/100.000sec - CCIR/PAL: 1/50 ~ 1/100.000sec
Lens:	6mm
Video output:	1Vp-p , 75 Ohms
Gamma:	0.45
Power supply :	DC12V (+/-) 0.5V
Power Consumption:	350 mA
Weatherproof Class:	IP 66
Housing:	Aluminum

Storage Temperature :

-30°C ~ 60°C

Operation Temperature :

-10°C ~ 45°C

* Pictures and specifications are subject to change without prior notice