

# DATA SHEET

---

PRODUCT:

15-CH21C

Type: Color  
Image Pick-Up Device: 1/4" CCD Image Sensor (Interline)  
Picture Elements: 512(H) x 492 (V), NTSC/EIA  
512(H) x 582 (V) PAL/CCIR  
Resolution: 350 Horizontal TV Lines  
Mini Illumination: 2 Lux  
Horiz. Sync. Frequency: NTSC/EIA 15,734KHz, CCIR/PAL 15,625KHz  
Vertical Frequency: NTSC/EIA 60Hz, CCIR/PAL 50Hz  
Clock Frequency: NTSC/EIA 19.0699MHz, CCIR/PAL 18.9375MHz  
Scanning System: Interlace 2:1  
S/N Ratio: More than 46dB  
Electronic Shutter: 1 to 1/100,000sec. Linear  
Lens: Pinhole 5.5mm f3.5  
Video Output: 1 Vp-p, 75 Ohms  
Audio Output: 2 Vp-p Max  
Gamma: 0.45  
PIR Sensor: YES  
Pules Counter: YES  
Alarm Contact: YES  
Dimensions: W60mm, H115mm, D30.8 (100 with bracket)mm  
Weight: 140g.  
Power Supply: 12 VDC (+/- 0.5V)  
Power Consumption: 140mA  
Storage Temperature: -30 to 60°C  
Operating Temperature: -10 to 45°C