



**CB25NV-IR**

CB25NV-IR Same as CB25NV, detects Infra Red Beams

<b>Optical Technology Base:</b>	1/3" CCC Color
<b>Image Size ( Horz x Vert in mm)</b>	4.82 x 3.64
<b>Picture Elements (Horz x Vert in mm):</b>	EIA/NTSC: 510 x 492 - CCIR/PAL: 500 x 582
<b>Resolution:</b>	380 Lines
<b>Pixels:</b>	290.000
<b>Minimum Illumination:</b>	0.1 Lux
<b>Horizontal Sync Frequencies :</b>	EIA/NTSC: 15.734 - CCIR/PAL: 15.625
<b>Vertical Frequencies :</b>	EIA/NTSC: 60 - CCIR/PAL: 50
<b>Clock Frequencies :</b>	EIA/NTSC: 19.0699 - CCIR/PAL: 18.9375
<b>Scanning:</b>	2:1 Interlace
<b>Sync System:</b>	AC Power with Line Lock
<b>S/N Ratio:</b>	46 dB
<b>Electronic Shutter:</b>	1/10000 / Sec Linear
<b>Auto Iris Lens:</b>	DC Drive/ AES / Video Drive
<b>Lens Mount :</b>	C and CS
<b>Gamma :</b>	0.45
<b>White Balance :</b>	Auto Tracing
<b>Back Light Compensation:</b>	Switchable
<b>Auto Gain:</b>	Switchable
<b>Dimensions mm :</b>	100 x 50 x 50
<b>Weight :</b>	250g
<b>Power Supply :</b>	12V DC Nominal
<b>Power Consumption :</b>	150mA
<b>Storage Temperature:</b>	-30°C to +60°C

\* Pictures and specifications are subject to change without prior notice