



**CC32B - High Resolution B/W Camera 600 TVL**

<b>Optical Technology Base:</b>	1/3" CCD B/W
<b>Image Size ( Horz x Vert in mm)</b>	4.82 x 3.64
<b>Picture Elements (Horz x Vert in mm):</b>	EIA/NTSC: 510H x 492V - CCIR/PAL: 500H x 582V
<b>Resolution:</b>	600 Lines
<b>Minimun Illumination:</b>	0.05 Lux
<b>Vertical Frequencies :</b>	EIA/NTSC: 60Hz - CCIR/PAL: 50Hz
<b>Scanning:</b>	2:1 Interlace
<b>S/N Ratio:</b>	52 dB
<b>Electronic Shutter:</b>	1/120.000 / Sec Linear
<b>Auto Iris Lens:</b>	DC Drive/ AES / Video Drive
<b>Video Output :</b>	1V p-p, 75 ohms
<b>Audio Output :</b>	Max 2V p-p, 50 ohms
<b>Gamma :</b>	0.45
<b>White Balance :</b>	Auto Tracing
<b>Back Light Compensation:</b>	ON/OFF/Switchable
<b>Auto Gain:</b>	ON/OFF/Switchable
<b>Mirror Reverse Picture:</b>	NO ( ON OFF Switchable )

<b>Digital Zoom:</b>	2X
<b>Dimensions mm :</b>	50.5 x 50.5 x 66
<b>Weight :</b>	265g
<b>Power Supply :</b>	12VDC (+/- 0.5V)
<b>Power Consumption :</b>	150mA
<b>Storage Temperature:</b>	-30°C to +60°C

\* Pictures and specifications are subject to change without prior notice