

WAT-902DM3 DSP Monochrome Camera

【SPECIFICATIONS】

Model	WAT-902DM3 (EIA/CCIR)
Pick-up element	1/3inch interline transfer CCD image sensor
Number of total pixels	811(H)×508(V):(EIA) 795(H)×596(V):(CCIR)
Number of effective pixels	768(H)×494(V):(EIA) 752(H)×582(V):(CCIR)
Unit cell size	6.35μm(H)×7.4μm(V):(EIA) 6.5μm(H)×6.25μm(V):(CCIR)
Scanning system	2:1 interlace
Synchronizing system	Internal
Video output	Composite video, 1Vp-p, 75ohm Unbalanced
Resolution(Horizontal)	570TV lines(Center)
Minimum illumination	0.002 lx. F1.4 (AGC HI)
Gamma correction	0.45, 1.0(Switchable with internal switch)
AGC	HI:8~40dB, LO:8~22dB
S/N ratio	52dB (AGC OFF=8dB, γ=1.0)
AE mode	OFF:1/60(EIA), 1/50(CCIR), FL:1/100(EIA), 1/120(CCIR), EI:1/60~1/100,000sec.(EIA), 1/50~1/100,000sec.(CCIR)
Back light compensation	ON/OFF selectable
Lens mount	CS-mount
Installation screw	U 1/4inch (D=5mm) (Top/Bottom)
Connection terminal	Video out(BNC), Power, Auto iris(Video/DC auto. selection)
Power supply	DC +9.0~15.0V
Current	Max. 120mA
Operating temperature	-10 ~ +40 (w/o condensation)
Storage temperature	-30 ~ +70 (w/o condensation)
Dimensions	35.5(W)×36.0(H)×64.0(L)mm
Weight	Approx. 90g
Accessories	DC-plug(WPDC12), Iris-plug(AIC-G), Hex. wrench

【DIMENSIONS】 (mm)

